

# Safety Data Sheet

## Anhydrous Ammonia

US Cylinder Gas

Alsip, IL



### Section 1: Product and Company Identification

**US Cylinder Gas**

Alsip, IL

Product Code: **Anhydrous Ammonia**

Part Number: Anhydrous Ammonia

**Synonyms:**

**Recommended Use:** Industrial use. Use as directed.

**Usage Restrictions:**

### Section 2: Hazards Identification



## Danger

Hazard Classification:

Acute Dust Inhale Toxicity (Category 4), H332  
Acute Gas Inhale Toxicity (Category 4), H332  
Acute Vapor Inhale Toxicity (Category 4), H332  
Eye Effects (Category 1), H318  
Flammable (Category 1), H220  
Gases Under Pressure, H280

Hazard Statements:

Specific target organ toxicity (Single Exposure) (Category 3), H335  
H332: Harmful if inhaled  
H318: Causes serious eye damage  
H220: Extremely flammable gas  
H280: Contains gas under pressure; may explode if heated  
H335: May cause respiratory irritation;  
CGA-HG04: MAY FORM EXPLOSIVE MIXTURES WITH AIR.

Precautionary Statements

P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing.  
 P271+P403: Use and store only outdoors or in a well-ventilated place.  
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
 P381: Eliminate all ignition sources if safe to do so.  
 CGA-PG02: Protect from sunlight when ambient temperature exceeds 52C (125F).  
 CGA-PG05: Use a back flow preventive device in the piping.  
 CGA-PG06: Close valve after each use and when empty.  
 CGA-PG10+CGA-PG20: Use only with equipment of compatible materials of construction and rated for cylinder pressure.  
 CGA-PG12: Do not open valve until connected to equipment prepared for use.  
 CGA-PG27: Read and follow the Safety Data Sheet (SDS) before use.

### Section 3: Composition/Information on Ingredients

<b>CAS #</b>
7664-41-7

Chemical Substance	Chemical Family	Trade Names
AMMONIA, ANHYDROUS	Inorganic gases	ANHYDROUS AMMONIA; AMMONIA GAS; AMMONIA; SPIRIT OF HARTSHORN; AMMONIA, ANHYDROUS, LIQUIFIED; UN 1005; H3N

### Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Thoroughly clean and dry contaminated clothing before reuse. Destroy contaminated shoes.	Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Gas: Not a likely route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention. Wear personal protective equipment if gas still present.	For inhalation, consider oxygen.

### Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray.	Nitrogen dioxide, ammonium nitrate	<ul style="list-style-type: none"> <li>▪ Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply, with full-body encapsulating, chemical protective suit.</li> <li>▪ Wear protective gear with respiratory support.</li> </ul>

## Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet.	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	Stop leak if possible without personal risk. Reduce vapors with water spray. Do not get water directly on material. Do not get water inside container. Trap spilled material at bottom in deep water pockets, excavated holding areas or within sand bag barriers.

Methods for Cleanup	Other Information
Small spills: Flood with water. Large spills: Dike for later disposal. Collect spilled material using mechanical equipment. Dike for later disposal. Add dilute acid. Absorb with sand or other non-combustible material. Collect runoff for disposal as potential hazardous waste. Do not direct water at source of leak of liquid ammonia.	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

## Section 7: Handling and Storage

Handling	Storage
Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.

## Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
AMMONIA, ANHYDROUS: 50 ppm (35 mg/m <sup>3</sup> ) OSHA TWA 35 ppm (27 mg/m <sup>3</sup> ) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 25 ppm ACGIH TWA 35 ppm ACGIH STEL 25 ppm (18 mg/m <sup>3</sup> ) NIOSH recommended TWA 10 hour(s) 35 ppm (27 mg/m <sup>3</sup> ) NIOSH recommended STEL

### Engineering Controls

Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves.	Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply, with full-body encapsulating, chemical protective suit.

### General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

## Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor
Gas	Colorless	Colorless	N/A	Gas, liquid	Pungent odor
Taste	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits
N/A	Not available			1204 F (651 C)	0.28

Lower Explosive Limits	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity
0.15	-27 F (-33 C)	-108 F (-78 C)	6658 mmHg @ 21 C	0.5967 (Air=1)	Not applicable (gas); 0.682 @ -33.4 C (liquefied gas)

Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity	Molecular Weight
38% @ 20 C	11.6 (1.0 N solution)	1-5 ppm	Not applicable	0.255 mPa.s (0.255 centipoises) @ -33.5 C (liquefied gas)	17.03

Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
N-H3	0.7067 g/L @ 25 C	Not available	Not available	Not applicable	Soluble : Methanol, ethanol, chloroform, ether, organic solvents

## Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and pressure.	High temperatures, electric discharge, electric sparks, welding, other ignition sources. Minimize contact with material. Avoid inhalation of material or combustion by-products. Containers may rupture or explode if exposed to heat.	Acids, combustible materials, metals, oxidizing materials, metal salts, halo carbons, halogens, amines, reducing agents, cyanides, bases

Hazardous Decomposition Products	Possibility of Hazardous Reactions
Ammonia, oxides of nitrogen	Will not polymerize.

## Section 11: Toxicology Information

### Acute Effects

Oral LD50	Dermal LD50	Inhalation
2000 ppm/4 hour(s) inhalation-rat LC50	Not established	Burns, severe irritant, pulmonary edema at concentrations over 1500 ppm

Eye Irritation	Skin Irritation	Sensitization
Burns, blindness	Burns, liquefied gas can cause frostbite	Acute toxicity, Category 3, inhalation; H331: Toxic if inhaled. Skin corrosion, Category 1B; H314: Causes severe skin burns and eye damage.

### Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not listed	Available.	Not established	No data

## Section 12: Ecological Information

### Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Acute LC50 0.88 mg/L 96 hour(s) Orangethroat; 1600 ug/L 96 hour(s) LC50 (Mortality) Common jollytail (Galaxias maculatus) Invertebrate toxicity: 7700 ug/L 96 hour(s) LC50 (Immobilization) Ark shell (Anadara granosa)	Not available	Not available	Not available

Algal toxicity: 2100-2300 ug/L NR hour(s) (Abundance) Algae, phytoplankton, algal mat (Algae) Phyto toxicity: 16500 ug/L 30 hour(s) (Abundance) Common water-nymph (Najas guadalupensis) Other toxicity: Not available			
--	--	--	--

### Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations.

### Section 14: Transportation Information

#### U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Ammonia, anhydrous	UN1005	2.2, 2.3	Not applicable	2.3; 8	Forbidden	Forbidden	Toxic-Inhalation Hazard Zone D

#### Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
AMMONIA, ANHYDROUS; or ANHYDROUS AMMONIA	UN1005	2.3; 8	Not applicable

### Section 15: Regulatory Information

#### U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
100 LBS RQ	500 LBS TPQ	100 LBS RQ

#### SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

#### SARA 372.65

AMMONIA, ANHYDROUS

#### OSHA Process Safety

10000 LBS TQ

#### State Regulations

**CA Proposition 65**  
Not regulated.

#### Canadian Regulations

**WHMIS Classification**  
A, B1, D1A, E

#### National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Listed on inventory.	Not listed.	Not determined.

## Section 16: Other Information

<b>NFPA Rating</b>
HEALTH=3 FIRE=1 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard