Safety Data Sheet

Helium/Argon, mixture US Cylinder Gas Alsip, IL



Section 1: Product and Company Identification

US Cylinder Gas

Alsip, IL

Product Code: Helium/Argon Mixes

Part Number: He/Ar Mixes

Synonyms: He/Ar 50/50, He/Ar 75/25, Ar/He 75/25

Recommended Use: Industrial use. Use as directed.

Usage Restrictions:

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure, H280

Simple Asphyxiant, OSHA-H01

Hazard Statements: H280: Contains gas under pressure; may explode if heated

OSHA-H01: MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary Statements

P202: Do not handle until all safety precautions have been read and understood.

P271+P403: Use and store only outdoors or in a well-ventilated place.

CGA-PG02: Protect from sunlight when ambient temperature exceeds 52C (125F).

CGA-PG05: Use a back flow preventive device in the piping. CGA-PG06: Close valve after each use and when empty.

CGA-PG10+CGA-PG20: Use only with equipment of compatible materials of

construction and rated for cylinder pressure.

CGA-PG12: Do not open valve until connected to equipment prepared for use.

Date of Preparation: 2/20/2024 1:37:24 PM

CGA-PG27: Read and follow the Safety Data Sheet (SDS) before use.

US Cylinder Gas page 1 of 6
Part Number: He/Ar Mixes

Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

Section 3: Composition/Information on Ingredients

	CAS#	Concentration
Argon	7440-37-1	22.5 - 82.5%
Helium	7440-59-7	22.5 - 82.5%

	Chemical Substance	Chemical Family	Trade Names
Argon	ARGON, COMPRESSED	Inorganic gases	ARGON; UN 1006; AR
Helium	HELIUM	Inorganic gases	HELIUM GAS; HELIUM COMPRESSED; HELIUM-4; ATOMIC HELIUM; UN 1046; He

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Argon	Not applicable route of exposure	Flush eyes with plenty of water.	Not applicable route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Helium	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters	
Argon	Non-flammable gas	Not applicable	■ N/a ■ N/A	
Helium	Non-flammable. use suitable extinguishing media for surrounding fire.	Non-flammable	Non-flammablenon-flammable	

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Argon	Keep unnecessary people away, isolate hazard area and deny entry.	None known.	Stop leak if possible without
	Stay upwind and keep out of low areas.		personal risk.
Helium	Keep unnecessary people away, isolate hazard area and deny entry.	Avoid soil, waterways, drains	Stop leak if possible without
	Stay upwind and keep out of low areas.	and sewers	personal risk.

	Methods for Cleanup	Other Information
Argon	Leaks may be detected by a soapy-water solution.	
Helium	Stop leak, evacuate area. Contact emergency personnel.	None

Section 7: Handling and Storage

	Handling	Storage
Argon	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Avoid using in confined spaces.
Helium	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.

US Cylinder Gas page 2 of 6
Part Number: He/Ar Mixes

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Argon	ARGON, COMPRESSED: ARGON: ACGIH (simple asphyxiant)
Helium	HELIUM: ACGIH (simple asphyxiant)

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Argon	Eye protection not required, but recommended.	Protective clothing is not required. Wear appropriate chemical resistant gloves.	N/a
Helium	Eye protection not required, but recommended.	Protective clothing is not required. Protective gloves are not required.	Non-flammable

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor
Argon	Gas	Colorless	Colorless	N/A	Gas	Odorless
Helium	Gas	Colorless	Colorless	N/A	Gas	Odorless
	Taste	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits
Argon	Taste Tasteless	Flash Point Not flammable	Flammability		_	

	Lower Explosive Limits	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity
Argon	Nonflammable	-303 F (-186 C)	-308 F (-189 C)	500 mmHg @ -190 C	1.38 (Air=1)	Not applicable
Helium	Nonflammable	-452 F (-269 C)	-458 F (-272 C) @ 26 atm	1719 mmHg @ - 268 C	0.138 (Air=1)	Not applicable

	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity	Molecular Weight
Argon	3.36% @ 20 C	Not applicable	Not available	Not applicable	0.0225 cP @ 25 C	39.948
Helium	0.94% @ 0 C	Not applicable	Not available	Not applicable	0.02012 cP @ 26.8 C	4.0026

	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Argon	AR	1.784 g/L @ 0 C	Not available	100%	Not applicable	Soluble : Organic solvents
Helium	He	0.1785 g/L @ 0 C	Not available	100%	Not applicable	Insoluble : Not available

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Argon	Stable at normal temperatures and pressure.	Protect from physical damage and heat. Containers may rupture or explode if exposed to heat.	No data available.

	Stability	Conditions to Avoid	Incompatible Materials
Helium	Stable at normal temperatures and pressure.	Protect from physical damage and heat. Containers may rupture or explode if exposed to heat. Keep liquid helium from contact with air.	No data available.

	Hazardous Decomposition Products	Possibility of Hazardous Reactions		
Argon	No data available.	Will not polymerize.		
Helium	Miscellaneous decomposition products	Will not polymerize.		

Section 11: Toxicology Information

Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Argon	Not established	Not established	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma
Helium	Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, fatigue, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

	Eye Irritation	Skin Irritation	Sensitization
Argon	No information on significant adverse effects	No information on significant adverse effects	
Helium	Liquid: frostbite, blurred vision	Liquid: frostbite	Difficulty breathing

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Argon	Not established	Not established	Not established	No data
Helium	Not available	Not available	Not available	No data

Section 12: Ecological Information

Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Argon	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Helium	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Argon	Dispose in accordance with all applicable regulations.
Helium	Dispose in accordance with all applicable regulations.

US Cylinder Gas page 4 of 6
Part Number: He/Ar Mixes

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

Shipping Name	Compressed gas, n.o.s. (Argon, Helium)
UN Number	UN1956
Hazard Class	2.2
Hazard Information	NonFlammable Gas

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Argon	Argon, compressed	UN1006	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
Helium	Helium, compressed	UN1046	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Argon	Argon, compressed	UN1006	2.2	Not applicable
Helium	Helium, compressed	UN1046	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40
Argon	Not regulated.	Not regulated.	Not regulated.
Helium	Not regulated.	Not regulated.	Not regulated.

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Argon	Yes	No	No	No	Yes
Helium	Yes	No	No	No	Yes

SARA 372.65

Argon	Not regulated.
Helium	Not regulated.

OSHA Process Safety

Argon	Not regulated.
Helium	Not regulated.

State Regulations

	CA Proposition 65
Argon	Not regulated.
Helium	Not regulated.

Canadian Regulations

	WHMIS Classification
Argon	A
Helium	A

National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)

US Cylinder Gas page 5 of 6

Argon	Listed on inventory.	Not listed.	Listed on inventory.
Helium	Listed on inventory.	Not listed.	Not determined.

Section 16: Other Information

	NFPA Rating
Argon	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA
Helium	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA

^{0 =} minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard